



Adhesion promoters

## TC AGGRAPPANTE



**TC AGGRAPPANTE** Adhesive Promoter is a paste consisting of dispersion copolymerization of vinyl in emulsion and carbonate aggregates in continuous granulometric curve from 0 to 2 mm. Specific to obtain rough surfaces suitable for receiving the next layer of plaster or of smoothing compound.



RADON FREE



RESTORATION



RESISTANT



CEMENT FREE



VERSATILE



HIGHLY ADHESIVE



QUICK



LIGHT



REVERSIBLE



EASY



GREEN BUILDING



CONSOLIDATING TREATMENT

## FEATURES

**TC AGGRAPPANTE** is an Adhesive Promoter, pre-packaged paste, specific to generate an adhesive layer between the substrate and subsequently laid materials such as plasters or smoothing compounds. The composition is specific to ensure adhesion characteristics and the easy obtainment of a rough surface that will act as adhesion layer.

## FIELDS OF APPLICATION

**TC AGGRAPPANTE** Adhesive Promoter is specific to the formation of rough surfaces act to generate a connection between substrate and materials that will be laid later. It must be applied on all the compact or poorly absorbent surfaces (solid blocks or concrete cables and expanded clay pebbles, concrete block cells, lime or cement based substrates, reinforced concrete structures, magnesium wood).

## APPLICATION

**TC AGGRAPPANTE** Adhesive promoter can be applied manually, by roller or flat brush directly on the surface. The product may be used as such or with a maximum dilution of 20% by weight with water. Wait 24 hours before laying the following Plaster or smoothing compound layers to ensure the perfect grip and adhesion to the surface of **TC AGGRAPPANTE**.

## TECHNICAL DATA

PRODUCT TYPE	<b>Adhesive Promoter</b>
GRAIN SIZE CURVE (EN 1015-1)	<b>0 - 2 mm</b>
FRESH MORTAR APPARENT DENSITY (EN 1015-6)	<b>1420 kg/m<sup>3</sup></b>
ADHESION (EN 1015-12)	<b>&gt; 0.5 N/mm<sup>2</sup></b>
2010 CE LIMIT VALUE OF VOC (cat. A/a) 30 g/l	<b>Max VOCs Content 10 g/l</b>
WATER DILUTION	<b>maximum 1 l per package</b>
CONSUMPTION	<b>about 0.2 kg/m<sup>2</sup></b>
PACKAGING	<b>5 kg bucket</b>
STORAGE	<b>Keep in dry place up 12 months in original package</b>
APPLICATION TEMPERATURE	<b>from +5°C to +32° C</b>
REACH CLASSIFICATION	<b>See SDS</b>

## WARNINGS

- Product for professional use.
- Do not modify the product.
- Store the product in a dry place in the original sealed packages.
- Before using the product refer to the Safety Data Sheet.
- The data given correspond to the technical and application knowledge we have for proper use of the product, so it is recommended to carry out a practical test prior to in order to verify the suitability of the product for its intended use and consumption.
- Protect the surfaces from atmospheric phenomena, sun, wind, rain and frost.
- Since our company is not the executor of the works and can not intervene directly on the construction site conditions and on the methods of work execution, the indications given are to be considered as indicative and general, and therefore not binding for the same.
- The Company reserves the right to make the changes at any time without notice when it deems necessary.
- For more information and practical product demonstrations please consult our technical service.
- Always refer to the updated versions of the technical data sheets available at [www.tcs-srl.it](http://www.tcs-srl.it).